FA 30 620 15, FA 30 621 15






CURIOSITY-S







HS CODE
63079098
CARTON SIZE / PCS.
FA 30 620 15: 80 x 40 x 24 cm / 10 FA 30 621 15: 60 x 40 x 48 cm / 8
AET N°2777/10964-03/E11-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16096-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 30 620 15	FA 30 621 15
LG. / KG	1.50 m (connectors included) Max. 140 KG	
CE	EN 355:2002	
MAT.	PA 11 mm	
	45 mm	
	ALU FA 50 103 22B (20 mm) / FA 50 208 60 (60 mm)	ALU FA 50 103 22B (20 mm) / FA 50 208 11 (109 mm)
	**YES**	
+	PPE-R 11.063	
Kg	1.76 KG	2.52 KG



Largeur de l'absorbeur d'énergie
Width of the energy absorber
Ancho del absorbedor de energía
Larghezza del assorbitore di energia
Breite des Falldämpfers



Matière connecteurs
Material of connectors
Material de los conectores
Materiale connettori
Material der Verbinder



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten