Chemical protection

JERSETTE 301

Frequent contact | continous wear

CHEMICAL PROTECTION
TYPE B

EN388	EN ISO 374-1	EN407
2131X	TYPE B KPT	X1XXXX

CATEGORY 3

0334

DEXTERITY

EN ISO 21420:
5/5

FSC
100%
Latex from well-managed forests
FSC® C139818

Maximum comfort for long-term work in aggressive environments. Made from FSC® certified latex.

SPECIFIC ADVANTAGES

Comfort

- Freedom of movement, due to the anatomical shape and excellent comfort from the seamless textile support

Durability

- Good tear-resistance

Skin protection

- Good resistance to many diluted acids and bases

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Care for the environment

- FSC® certified latex
- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES

- Local Authorities (Cleaning)
- Aeronautics industry
- Construction Industry (Masons / Plasterers)

APPLICATIONS

- Preparing and pouring mortar and cement
- Work with composite materials (resins)
- Handling household detergents

Edit 05/02/2025

Chemical protection

JERSETTE 301

Frequent contact | continous wear

LEGENDS

EN388 — MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

2	1	3	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)

PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

EN ISO 374-1 — CHEMICAL RISKS

K: Sodium hydroxide 40%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%

TYPE B

PRODUCT DETAILS

Interior finish	Textile support
Exterior finish	Pebbled
Material	FSC® certified latex
Cuff characteristic	Feston Cuff
Colour.s	Blue
Thickness (mm)	1.15
European sizes	5 6 7 8 9 10

LOGISTIC DETAILS

Packaging	1 pair/bag 5 pairs/bag 50 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/05/22/0905 EX 01/05/22
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 05/02/2025