Chemical protection

ULTRANITRIL 358

Frequent contact | ultra-comfort wear

Designed with an embedded optimal grip to safely handle tasks in dry & greasy environments



ADVANCED GRIP TECHNOLOGY

CHEMICAL PROTECTION
TYPE A

EN388	EN ISO 374-1	EN ISO 374-5
3111A	TYPE A AJKOPT	

EN407		CATEGORY 3
X1XXXX	ISO 18889	0334

ISO 13997:	DEXTERITY
4.9 N	EN ISO 21420: 5/5

SPECIFIC ADVANTAGES

Thermal protection

- Added comfort and thermal insulation, due to the cotton-knit lining

Comfort

- Very supple glove providing high dexterity
- Good fingertips sensitivity

Productivity

- Optimal grip to improve productivity, reduce hand fatigue and enhance safety

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Care for the environment

- Plastic packaging optimized
- Recycled material in the packaging: 30 %

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Petrochemical industry
- Cosmetics and Pharmaceutical industry
- Agriculture sector

APPLICATIONS

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Chemical product blending
- Handling drums of chemical products
- Handling in laboratories

Edit 02/12/2024

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

Chemical protection

ULTRANITRIL 358

Frequent contact | ultra-comfort wear

LEGENDS

EN388 — MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

3	1	1	1	A	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)

PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

EN ISO 374-1 — CHEMICAL RISKS

TYPE A

A: Methanol
J: n-Heptane
K: Sodium hydroxide 40%
O: Ammonia 25%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%

ISO 18889 — PROTECTION FROM PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

EN ISO 374-5 — MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Textile support Mapa Technology
Exterior finish	Reinforced grip
Material	Nitrile
Colour.s	Green
Length (cm)	36
Thickness (mm)	1,1
European sizes	6 7 8 9 10 11

LOGISTIC DETAILS

Packaging	12 pairs/bag 72 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/05/24/1139
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 02/12/2024