Cut protection

KRYTECH 586

High risk - ISO D

High-performance protection for intricate handling in reasonably clean environments

CUT PROTECTION
LEVEL D

EN388

4X43D

CATEGORY 2

ISO 13997:

18.6 N

DEXTERITY

EN420:
5/5

SPECIFIC ADVANTAGES

Cut protection

- Optimal cut resistance

Comfort

- Excellent dexterity due to the precise fit
- Added comfort and flexibility

Skin protection

- Contains traces of DMF in compliance with occupational exposure limits

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability

- Washable up to 3 times at 60°C , allowing to extend glove lifespan, reduce costs and waste.

Practical

- A visible indicator in blue textile to easily identify the cut-performance level in the workplace Washable until 3 cleaning cycles (see laundering and drying conditions)

INDUSTRIES

- Automotive/mechanical industry
- Local Authorities (Technical Maintenance)
- Construction Industry (Roofers/Tilers/Glazers)
- Plastics industry

APPLICATIONS

- Handling and fitting windows
- Post-injection material removal
- Maintenance work with risk of cuts
- Assembly of thin metal sheets
- Finishing sharp parts
- Handling metal parts

Edit 28/11/2024

Cut protection

KRYTECH 586

High risk - ISO D

LEGENDS

EN388

MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

4	X	4	3	D	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour.s	Grey Blue
Length (cm)	24-30
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.3E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.5E+10 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0209
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 28/11/2024