

G-TEK® - POSIGRIP MAX® 18G SEAMLESS KNIT GLOVE WITH HPPE/ NYLON/SPANDEX/METAL WIRE BLENDED LINER, POSIGRIPMAX COATING ON PALM & FINGERS - CUT D.

- PosiGrip® MAX Technology is a new, highly innovative coating designed to offer exceptional grip, durability, and comfort.
- PosiGrip® MAX gloves require up to 40% less force than traditional Nitrile (NBR) gloves for pulling and catching tasks, while offering near-zero oil permeability, to keep hands dry and clean.
- With PosiGrip® MAX, combine superior grip in oily conditions with a second-skin feel, without compromising on protection.
- 18 gauge for exceptional dexterity.
- Up to 30% lighter than standard gloves, ideal for prolonged use.
- Integrated thumb reinforcement for longer life and added protection.
- The knitted cuff prevents dirt and debris from entering the glove.

APPLICATIONS

- Aeronautics
- Assembly of metal parts and components
- Finishing work
- Glass manufacture
- Cutting small oiled parts

CARE INSTRUCTIONS

It is advisable to clean the gloves in temperate water with a maximum temperature of 40°C. A mild non-ionic detergent should be used. A drying time of 5-10 minutes should be used. Low temperature tumble drying - maximum temperature 140°F (60°C)



TECHNICAL SPECIFICATIONS

MATERIAL	Liner: HPPE & Nylon & Spandex & Metal Wire / Posigrip-Max coating on Palm & Fingers
CONSTRUCTION	Seamless knit
COLOUR	Liner: ■ Purple / Coating ■ Black
WRIST STYLE	Knit wrist
SIZES	6 - 11
PACKAGE	Individual pair paper wrap, 12 pairs per bag, 120 pairs per case.
COO	China

PERFORMANCE PROPERTIES

EN388: 4X42D							
ABRASION	0	1	2	3	4	-	-
CUT (2003)	0	1	2	3	4	5	X
TEARING	0	1	2	3	4	-	-
PUNCTURE	0	1	2	3	4	-	-
CUT (ISO 13997)	A	B	C	D	E	F	X

DIMENSIONS (IN/CM)

	6	7	8	9	10	11
A	8.9 / 22.5	9.2 / 23.5	9.6 / 24.5	10 / 25.5	10.4 / 26.5	10.8 / 27.5
B	2.9 / 7.5	3 / 7.7	3.3 / 8.5	3.4 / 8.7	3.47 / 8.8	3.55 / 9
H	■ Purple	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

