



EN ISO 20471 (2013) + A1 (2016)



EN 1149-5 (2008)



EN ISO 14116 (2015)




Index 1

PRODUCT DATA SHEET



THE + PRODUCT


Lock system for microphone.



Two front hook and loop fastenings.



Heat transferred microbeads retroreflective strips to avoid any retention of molten material.



REFERENCES

- GILETSILEX1JF
- GILETSILEX1OF
- GILETSILEX1RF



FRONT



BACK

SIZE

M / L / XL / XXL

Other size, on demand.

CARE



Wash at 40°C (according to ISO 6330 4N).

PRODUCT DESCRIPTION

- Two front fireproof hook and loop fastenings.
- One lock system for microphone.
- Jacket fully piped.
- Two heat transferred RETHIOTEX® 26 500 microbeads retroreflective strips around the body.



SILEX SAFETY VEST

RAW MATERIALS

OUTER FABRIC

- Nittex Stop Flam fireproof and antistatic knit. 98% polyester and 2% carbon. Weight: 120 g/sqm.

RETROREFLECTIVE TRANSFER

- Flame retardant microbeads retroreflective RETHIOTEX® 26 500 transfer. 50 washing cycles at 60°C (according to ISO 6330 6N).

STORAGE

The SILEX safety vest is packaged in individual transparent packaging.

The product must be stored in its original packaging in a cool, dry place away from light.

CARE

Wash at 40°C.

Do not bleach, iron, dry clean or tumble dry.



Wash at 40°C (according to ISO 6330 4N).

COMPLIANCE AND EXAMINATION CERTIFICATE

Compliance with the essential safety requirements has been verified using the following harmonised standards:

- EN ISO 13688 (2013) for protective clothing - general requirements.
- EN ISO 20471 (2013) + A1 (2016) for high visibility warning clothing.
- EN ISO 14116 (2015) for protection against limited flame.
- EN 1149-5 (2008) for protection against electrostatic discharges.

The examination certificate was awarded by CENTEXBEL to the following model of personal protective equipment:

GILETSILEX1

N°033/2020/0073