

RUNNER - FLEX S3
HI CI SRC
Réf. : 70805



Suitable for :	Inside/Outside
Type :	Ankle shoe
Activity :	Construction / Storage, Logistic, Transport / Electronic Industry, ESD
Upper :	Water resistant full supple leather and CORDURA® material
Lining :	ARTICO® black color, up to the toes, slipper feeling
Tongue :	Bellows tongue in ON STEAM® microfibre, lining ARTICO® and padded with 10mm thick foam
Ankle protection :	CORDURA® material, ARTICO® lining and padded with 10mm thick foam
Fastening :	Round polyester black laces with "Quick lock" system
Toe cap :	Ultralight, extra large, made of athermal and non-magnetic composite material, with crush and impact resistance of 200 joules
Midsole :	Composite FLEX SYSTEM®, anti-magnetic and thermal insulated
Insole :	Thermoformed in active carbon dual density foam, antistatic, ESD and antibacterial FRESH TECH®
Sole :	PU 2D, TECH SOLE® ankle anti-twist system, oil resistant FO, antistatic, HI-CI, built-in PU overcap in the front (bumper effect)
Sole pattern :	Multi-purpose cleated indoor/outdoor outsole, well-defined heel, cleated arch, SRC standard
Weight (Kg/pair) :	1.257 size 42
Colors :	Black upper and dark grey/light grey outsole
Sizes :	35-48 (2-13)
Standard :	EN ISO 20345:2011 SRC / EN 61340-4-3 / DGUV 112-191
CE certificate of conformity N° :	0075/020/161/04/18/0585 EXT 08/04/18
Special features :	Quick fastening system "Quick lock"
Special features 2 :	Reflective piping on the heel part
Special features 3 :	A TPU strip injected directly over the toecap makes it invisible and very comfortable.

SPECIAL FEATURES



Integral 100% composite
(Air System + Light System + Flex System)



Metal free, non magnetic



Water absorption and
penetration resistance of upper (WRU)



Electro Static Discharge Standard
EN 61340-5-1



Orthopedic insole



Embout composite
Composite toe cap



GENERAL FEATURES



Antistatic properties (A)



Heel energy absorption (E)



Abrasion resistance



Crampon sole



200 joules extra-wide toe cap



Heat-insulated sole (HI)



Cold-insulated sole (CI)



Perforation-resistance 1100 N (P)



Hyper-ventilated lining