technical file

Ref: 07JERICA

Mixed lace-up shoe



Ref: 7834

Norms

EN ISO 20345: 2011 S3
Steel safety toe-cap 200 J
Steel antiperforation midsole 1100N
Norm SRC*

Informations

Size: 36-47
Ref:7834: Black color
Weight of one pair 37: 0,880kg
Weight of one pair 42: 1,100kg
-
-

Upper's description

Leather, microfiber & canvas upper
Lace-up shoes
100% polyamide quarter lining
Removable anti-bacterial textile & foam insock

Sole's description

Injected upper
PU double density (polyurethan outsole)
Polyurethan midsole

Technologies

Antistatic shoe
Fuel oil resistant shoe
VPS System (= Suspended arch support)
-

Use

Industry
Logistics
Services
Trade/Distribution
-
-
-
-
-
-

Restriction

Warm floor > 100°
-

Packaging

In individual box, in 10 pairs' package

*Coefficient d'adhérence SRC (SRA+SRB) valeurs minimum requises:

Sol	Lubrifiants	Position à plat	Position talon	Symbole
Céramique	Détergent	≥0,32	≥0,28	SRA
Acier	Glycérine	≥0,18	≥0,13	SRB

Version V3 - Mis à jour Avril 2013 - Réalisation PARADE