REBEL™ SELF RETRACTING LIFELINE (SRL)



TOTAL COMPLIANCE. ABSOLUTE CONFIDENCE.

PROTECTA

TRUSTED, QUALITY FALL PROTECTION OVER 50 YEARS

PRODUCT SHEET

2011

DEPENDABILITY
YOU CAN RELY ON EVERY DAY

Protecta® continues to set the standard for performance and value.

The Rebel™ SRL line is built to last providing an economical fall protection solution without compromising performance or safety!



Durable

- Built to last
- Heavy-duty housing types
  - Aluminium
  - Thermoplastic
- Stackable

Markets Served

- Commercial Construction
- Residential Construction
- Industry & Manufacturing
- Roofing
- Steel erection

And more !

Reliable

- 140 kg capacity
- Side cable exit
- Double swivel
- Fall indicator hook

Easy to maintain

- The design of the SRL is made up of 30% parts less than usual SRL
- Several parts are common to different model sizes
- It makes the maintenance to be quicker and easier when the block needs to be maintained

Easy to inspect

- Internal design and fall indicator hook allow a competent person to visually perform the yearly inspection
- No need to send the SRL back to authorized service centers for yearly inspection

Sharp edge compliant

- Meets the last updated CE sharp edge certification for horizontal use

EXPLORE THE SYSTEM

140 kg Capacity

High capacity for operator and tools

Top Swivel

Limits lifeline twisting

Stackable

Housing design allows for stacking on work surfaces

Thermoplastic Housing

Lightweight, compact and durable

or

Aluminium Housing

Provides exceptional strength and durability



Ergonomic Carrying Handle

Built-in design makes transport, set-up and storage easy

Side Cable Exit

Enables smooth operation and reduces cable wear

Use of additional sling extension

Ref : 3500050 allows all Rebel to be used on horizontal and to meet CE sharp edge certification

Ergonomic Cable Handle

Provides added comfort and ease-of-use when making connections

Galvanized and SS Cable

Stainless steel option for added corrosion resistance

Swivel Hook

Limits lifeline twisting

Unique Packaging



Impact Indicator

Provides visual indication of Fall Arrest

Self Locking Snap Hook

Automatically closes and locks for added safety

1,633 kg Gate Capacity

Reduces chance of accidental disengagement (“roll-out”)

REBEL™ SELECTION TABLE

Reference	Length (m)	Depth (cm)	Width (cm)	Height (cm)	Weight (kg)	Housing type	Cable material
3590520	6	12	25	57	5,3	Plastic	Galvanised
3590530	6	12	25	57	6,7	Aluminium	Galvanised
3590521	10	12	25	57	5,6	Plastic	Galvanised
3590531	10	12	25	57	7,0	Aluminium	Galvanised
3590522	10	12	25	57	5,6	Plastic	Stainless Steel
3590532	10	12	25	57	7,0	Aluminium	Stainless Steel
3590570	15	12	28	61	7,5	Plastic	Galvanised
3590580	15	12	28	61	9,1	Aluminium	Galvanised
3590571	15	12	28	61	7,5	Plastic	Stainless Steel
3590581	15	12	28	61	9,1	Aluminium	Stainless Steel
3590610	20	14	33	65	10,0	Plastic	Galvanised
3590620	20	14	33	65	12,4	Aluminium	Galvanised
3590611	20	14	33	65	10,0	Plastic	Stainless Steel
3590621	20	14	33	65	12,4	Aluminium	Stainless Steel
3590650	25	14	33	65	13,0	Plastic	Galvanised
3590660	25	14	33	65	15,4	Aluminium	Galvanised
3590651	25	14	33	65	13,0	Plastic	Stainless Steel
3590661	25	14	33	65	15,4	Aluminium	Stainless Steel
3590690	30	14	33	65	13,4	Plastic	Galvanised
3590700	30	14	33	65	15,8	Aluminium	Galvanised
3590691	30	14	33	65	13,4	Plastic	Stainless Steel
3590701	30	14	33	65	15,8	Aluminium	Stainless Steel

A specific range of the Rebel™ SRL also exist with shorter length :

Web lifeline: Robust aluminium housing for length of 3m (ref.: AD111) to 6m (Ref.: AD120)

Lightweigth plastic housing for a 6m length (ref.: 3101041)

Cable Lifeline: Robust aluminium housing for a 4,5m length



©2011, Capital Safety

capital SAFETY

Capital Safety Group - Europa, Middle-East, Africa
Le Broc Center Z.I. 1re Avenue 5600 m B.P. 15
06511 Carros Le Broc Cedex - France
Tel : + 33 (0)4 97 10 21 11
Fax: + 33 (0)4 93 08 79 70
information@capitalsafety.com
www.capitalsafety.com

Capital Safety Group - Northern Europe
7, Christleton Court - Stuart Road - Manor Park
Runcorn Cheshire - WA7 1ST - UK
Tel : + 44 (0) 1928 571324
Fax: + 44 (0) 1928 571325
csgne@capitalsafety.com
www.capitalsafety.com