LIGHTS

2410
StealthLite™ Zone 0

Save as PDF

Peli lights - Zone 1 Lights - LED technology lights



Same features as the StealthLite 2400 but with the LED module that produces a true, bright collimated LED beam. The StealthLite 2410 LED Zone 0 is corrosion proof, resistant to extreme temperatures, and submersible. It is powered by 4 AA alkaline cells and certified to ATEX Zone 0 (Category 1). For hands-free operation, attach it to your hard hat with our optional helmet light holder.

Yellow Gray

Peli lights - Zone 1 Lights - LED technology lights

ANSI FL1 Specifications

	High	
LIGHT SOURCE.	LED	
BATTERIES	4 AA Alkaline (Not included)	
CHARGE TIME	N/A	
VOLTAGE	6	
LENGTH	17.8 cm (7")	
WEIGHT W/ BATTERIES	0.17 kg (6 oz.)	
WEIGHT W/O BATTERIES	0.1 kg (3.7 oz.)	

FL1 STANDARD	High	
LIGHT OUTPUT		
RUNTIME (hours/min)	7h 30m	
BEAM DISTANCE (meters)	161m	
PEAK BEAM INTENSITY (candela)	6500cd	

Materials

Body	Lens	Shroud	Switch Type
EXL	Polycarbonate Resin	ABS	One-handed safety switch operation

Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
	Stainless Steel and Phosphone Bronze	Ethylene Propylene	

Configuration

Cat. #	Description

Peli lights - Zone 1 Lights - LED technology lights Accessories

Cat. #	Description

Approvals

CE Ex - II 1 G Ex ia IIC T4 Ga, II 1 D Ex ia IIIC T135??C Da IP66
Certificate: ITS09ATEX26183X