*For any information, contact :*
**FRANCE SECURITE SAS**
585 Rue Alain Colas
CS 61856
29218 BREST CEDEX 1 - FRANCE
Tel : 02 98 80 25 35
www.france-securite.fr

*USER INSTRUCTIONS*

# DRY BASE C

**S234177**

Sécuritop

***Protective gloves against mechanical risks.***
***PU coating onto palm. Polyethylene UHMWPE liner with polyester, spandex, fiberglass. Knitted wrists.***
***Screen touch compatibility.***

*Notified body used for EU type certificate : SGS FIMKO OY (N°0598)*
*Takomotie 8, FI-00380 Helsinki, FINLAND*

*EN ISO 21420:2020: General requirements – Dexterity :* ***LEVEL 5***

*EN388:2016 + A1 :2018*
*(Levels taken on palm new gloves) :*

**4X42C**

1. **Abrasion : 4/4**
2. **Blade cut resistance : X/5**
3. **Tear strenght resistance : 4/4**
4. **Puncture resistance : 2/4**
5. **Cut resistance TDM : C/F**

For dulling during the cut resistance test, the coupe test results are only indicative while the TDM Cut Resistance test is the reference performance result.

**« X » means that the test has not been done or the performance not claimed.**

| Performance levels | Level 1 | Level 2 | Level 3 | Level 4 | Level 5 |
|---|---|---|---|---|---|
| Abrasion resistance (Number of cycles) | 100 | 500 | 2000 | 8000 | - |
| Coupe test : Blade cut resistance (Index) | 1.2 | 2.5 | 5.0 | 10.0 | 20.0 |
| Tear Strenght resistance (Newtons) | 10 | 25 | 50 | 75 | - |
| Puncture resistance (Newtons) | 20 | 60 | 100 | 150 | - |

| Performance levels according to EN ISO 13997 | Level A | Level B | Level C | Level D | Level E | Level F |
|---|---|---|---|---|---|---|
| Tomodynamometer "TDM " : Cut resistance (Newtons) | 2 | 5 | 10 | 15 | 22 | 30 |

For gloves with two or more layers, the overall classification does not necessarily reflect the performance of the outermost layer.

***This kind of glove does not protect against risks not written in this user instruction.***

Store in a cool dry place away from strong sunlight. The gloves are employed and intended to protective against mechanical risks of abrasion, TDM cut, tear, puncture of palm in working environment. The gloves meet the requirement for resistance to puncture, may not be suitable for protection against sharply pointed objects such as hypodermic needles.
The gloves are not to be used for chemical protection, naked flame, electrical protection or use where a risk of entanglement by moving parts.
This glove is not subject to aging if stored in appropriate conditions (humidity, temperature, ventilation, brightness)
The CE marking on this product means that it meets the requirements of Regulation (EU) 2016/425 on personal protective equipment for safety, comfort and strength.
Don't use in case of risk of being caught by a moving machine.
This glove doesn't contain substances known to be carcinogenic, toxic or likely to cause allergies to sensitive people.
The actual conditions of use may differ from those of tests carried out under laboratory conditions according to the requirements defined by the standards.

This glove is not washable.
Available from size 6 to size 11.

**The EU declaration of conformity can be accessed through http://conformites.frsecurite.fr**

Find our products range
on our E-Catalogue.

LE TRI FACILE PAPIER

*Made in China* *Ind 1*

*Pour tout renseignement, contacter :*
**FRANCE SECURITE SAS**
585 Rue Alain Colas
CS 61856
29218 BREST CEDEX 1 - FRANCE
Tel : 02 98 80 25 35
www.france-securite.fr

*NOTICE D'INFORMATIONS*

# DRY BASE C

**S234177**

Sécuritop

***Gants de protection mécanique renforcée à usage générale.***
***Enduction PU sur la paume. Support en polyéthylène UHMWPE avec du polyester, spandex, fibre de verre. Poignets bord-côtes.***
***Compatible écrans tactiles.***

*Organisme notifié ayant délivré l'AET : SGS FIMKO OY ( N°0598)*
*Takomotie 8, FI-00380 Helsinki, FINLAND*

*Norme EN ISO 21420:2020: Innocuité – Confort – Dextérité :* ***NIVEAU 5***

*Norme EN388:2016 + A1 :2018*
*(Niveaux obtenus sur la paume d'un gant neuf) :*

**4X42C**

1. **Abrasion : 4/4**
2. **Coupure par tranchage : X/5**
3. **Déchirure : 4/4**
4. **Perforation : 2/4**
5. **Résistance à la coupure TDM : C/F**

En cas de lame émoussée pendant le coupe-test, le résultat au coupe-test est seulement indicatif alors que le test TDM est la performance de référence.

**Le « X » signifie que l'essai n'a pas été réalisé et la performance n'est pas revendiquée.**

| Niveaux de performance | Niveau 1 | Niveau 2 | Niveau 3 | Niveau 4 | Niveau 5 |
|---|---|---|---|---|---|
| Résistance à l'abrasion (Nombre de cycles) | 100 | 500 | 2000 | 8000 | - |
| Résistance à la coupure par tranchage (Nombre de tours) | 1.2 | 2.5 | 5.0 | 10.0 | 20.0 |
| Résistance à la déchirure (Newtons) | 10 | 25 | 50 | 75 | - |
| Résistance à la perforation (Newtons) | 20 | 60 | 100 | 150 | - |

| Niveaux de performance selon l'EN ISO 13997 | Niveau A | Niveau B | Niveau C | Niveau D | Niveau E | Niveau F |
|---|---|---|---|---|---|---|
| Tomodynamomètre "TDM " : résistance à la coupure (Newtons) | 2 | 5 | 10 | 15 | 22 | 30 |

Pour les gants comportant deux couches ou plus, la classification globale ne reflète pas nécessairement les performances de la couche la plus externe.

***Ce type de gants ne protège pas des risques non mentionnés sur cette notice.***

Stocker dans un endroit sec, à l'abri de la lumière. Les gants sont utilisés et destinés à protéger contre les risques mécaniques d'abrasion, de coupure de TDM, de déchirure, de perforation de paume dans l'environnement de travail. Les gants répondent à l'exigence de résistance à la perforation, peuvent ne pas convenir pour la protection contre les objets pointus comme les aiguilles hypodermiques. Les gants ne doivent pas être utilisés pour la protection chimique, la flamme nue, la protection électrique ou l'utilisation où un risque d'enchevêtrement par des pièces mobiles. Les performances de conception ne peuvent pas être affectées de manière significative par le vieillissement lorsqu'il est stocké dans des conditions appropriées (humidité, température, ventilation, luminosité).
L'apposition du marquage CE sur ce produit signifie qu'il satisfait aux exigences prévues par le Règlement (UE) 2016/425 relatif aux équipements de protection individuelle concernant l'innocuité, le confort, la solidité. Ne pas utiliser en cas de risque de happement par une machine en mouvement. Ce gant ne contient pas de substances connues comme étant cancérigènes, ni toxiques, ni susceptible de provoquer des allergies aux personnes sensibles. Les conditions réelles d'utilisations peuvent différer de celles des essais réalisés en conditions de laboratoires selon les exigences définies par les normes.

Ce gant n'est pas lavable.
Disponible de la taille 6 à la taille 11.

**La déclaration UE de conformité est accessible sous http://conformites.frsecurite.fr**

Retrouvez notre sélection de produits sur
notre E-Catalogue.

LE TRI FACILE PAPIER

*Made in China* *Ind 1*